

VETASSURE 60 L



SMALL
FOOTPRINT
HUGE
CAPACITY

- CAPACITY 60 LITERS
- BUILT-IN OSMOTIC SYSTEM
- DOUBLE VACUUM PUMP
- DOUBLE MOTOR-OPERATED LOCKING SYSTEM
- INTEGRATED USB STORAGE DEVICE
- ON BOARD PRINTER
- QUIKSTEAM PATENTED TECHNOLOGY
- ADDITIONAL DRYING OPTION
- « START DELAY » OPTION
- B/S/N-CLASS CYCLES INCLUDED



VETASSURE 60 L STERILIZERS ARE SUPPLIED WITH:
TRAYS HOLDER | ALUMINIUM TRAYS | CLEANING SPONGE | 1 SILICONE INSULATED GLOVES | TUBES AND FITTING |
CD SOFTWARE | OSM03 PROTECTION FILTER

Sterilisation Table

DISPLAYED #, TEMPERATURE AND NAME	VETASSURE B60		VETASSURE B60 SI		STERIZABLE LOAD	WRAPPED/ OPEN
	TYPE	TOTAL TIME	TYPE	TOTAL TIME		
1 HELIX - B&D TEST	TEST	75'	TEST	45'	N/A	✗
2 VACUUM TEST		15'		15'		✗
3 121 °C HOLLOW WRAPPED	B	115'	B	73'	Solid Small porous Simple hollow Narrow lumen Multiple casing	✓
4 134 °C HOLLOW WRAPPED		110'		69'		✓
5 121 °C SOLIDS WRAPPED	S	100'	S	60'	Solid Small porous Simple hollow	✓
6 134 °C SOLIDS WRAPPED		95'		59'		✓
7 134 °C PRION	B	135'	B	72'	Load related to Creutzfeldt-Jakob disease	✓
8 134 °C POROUS		130'		89'	Full porous	✓
12 134 °C SOLIDS OPEN	N	105'	N	68'	Solid	✓

WEIGHT	Solids wrapped: 12 kg Porous: 6 kg
--------	---------------------------------------

NOTE: Narrow lumen is an item open on one side with length equal to 5 times (or more) the diameter.
Times are calculated in conditions of pre-warmed chamber.

TECHNICAL DATA

VETASSURE B60	VETASSURE B60 SI	
fractionated		TYPE OF VACUUM
-	✓	INTEGRATED STEAM GENERATOR
Bowie&Dick/Helix/Vacuum		TEST PROGRAMS
✓		BUILT-IN PRINTER
		M.T.S MEMORY TEST SYSTEM
		CONNECTION TO DATA LOGGER
		INTERNAL USB DATA LOGGER
		WATER QUALITY SENSOR
		INTEGRATED WATER PURIFICATION SYSTEM
135 kg	138 kg	WEIGHT
655Wx850Dx755H mm		OVERALL MEASURES (WITHOUT CABINET)
ø350x622 mm		CHAMBER SIZE
nr. 4 aluminium trays: 2 trays 310Wx550Dx25H mm 2 trays 220Wx550Dx25H mm		TRAY SIZES
230 V ± 10% (1 phase)	400 V ± 10% (3 phases)	SUPPLY VOLTAGE
50-60 Hz		MAINS FREQUENCY
11 Amp	13 Amp per phase	RATED POWER